

Chassis Specifications

For: 2015 WFJ33S, WFJ38S

FORD

Model	-----	F-53, Super Duty
GVWR	-----	22,000 lbs. (J33S)
GAWR, Front	-----	8,000 lbs
GAWR, Rear	-----	15,000 lbs.
GCWR	-----	26,000 lbs.
GVWR	-----	24,000 lbs. (J38S)
GAWR, Front	-----	9,000 lbs.
GAWR, Rear	-----	15,500 lbs.
GCWR	-----	30,000 lbs.
GVWR	-----	26,000 lbs. (Optional 16A on J38S)
GAWR, Front	-----	9,000 lbs.
GAWR, Rear	-----	17,500 lbs.
GCWR	-----	30,000 lbs.
Wheelbase	-----	208" (J33S), 248" (F38S)
Engine	-----	6.8L SOHC Three-Valve Triton V10 362 HP @ 4,750 RPM 457 lb.-ft. @ 3,250 RPM Electronic throttle
Emission Control System Certification	---	50-States
Alternator	-----	130-amp
Battery	-----	750 CCA, 78-amp hr., maintenance-free
Suspension, Front		
Type	-----	Monobeam axle w/multi-leaf tapered springs
Stabilizer Bar	-----	1.5" dia., Heavy-duty track bar
Shock	-----	Bilstein
Suspension, Rear		
Type	-----	Multi-leaf tapered springs
Stabilizer Bar	-----	1.40" dia.
Axle Ratio	-----	5.38 (22,000) 6.17 (24,000)
Shock	-----	Bilstein

SEE REVERSE SIDE FOR ADDITIONAL INFORMATION

Brakes	-----	Hydraulic, hydromax, 4-wheel ABS
Front	-----	Disc - 15.55" dia. (22,000) 15" (24,000)
Rear	-----	Disc - 15.55" dia. (22,000) 15" (24,000)
Parking	-----	Transmission mounted drum, foot apply, hand release
Fuel System	-----	80-gallons
Provision for Aux. Generator	-----	Port in fuel level sending unit
Transmission	-----	TorqShift five-speed automatic overdrive Tow/haul feature Mechanical "Lock-up" in park position
Tire		
Front/Rear	-----	235/80R 22.5G (w/22,000-lb GVWR)
max. Capacity - Front/Rear	-----	4,675/4,410 @ 110 psi
Front/Rear	-----	255/80R 22.5G (w/24,000-lb GVWR)
max. Capacity - Front/Rear	-----	5,205/4,805 lbs. @ 110 psi
Wheel	-----	22.5" X 7.5" aluminum, Alcoa Dura-Bright (4) 22.5" X 7.5" steel (2)
Frame	-----	Ladder-type, single channel, 50,000 psi steel
Section Modulus	-----	9.46 (full-section channel, front to rear)
Instrumentation	-----	Speedometer, odometer, tachometer; oil pressure, coolant temperature, trans oil temperature and fuel gauges directional signal, high beam and charge indicator lights, and various warning lights
Chassis Warranty	-----	See Ford Owner's manual Motor Home Customer Assistance Center: 800-444-3311

WINNEBAGO INDUSTRIES RESERVES THE RIGHT TO CHANGE FEATURES AND SPECIFICATIONS WITHOUT PRIOR NOTICE

COPYRIGHT 2012

WINNEBAGO INDUSTRIES, INC., P.O. BOX 152, FOREST CITY, IOWA 50436